


RM-4A+(E-4+)


Tire Size: 27.00R49



سنگ ریزه



صخره ای



سطوح سخت



RM-4A+(E-4+)

The RM-4A+ is the next generation of Goodyear haulage tires where severe operating conditions demand optimum durability and performance.

Tire Size: 27.00R49

Available in ply ratings: * *

RM-4A+(E-4+)

Tire Size: 27.00R49

FEATURES

Extra deep tread pattern

A sidewall scallop is used for reduced temperature build-up

High Angle/Non-Directional tread pattern

Interlocking stability blading

High Net-to-Gross tread pattern

BENEFITS

Helps provide longer tread wear

Allows for a higher TMPH rating for improve overall performance

Helps provide traction both forward and backward

Helps improve footprint stability and addition heat relief

Places more wearable tread on the ground

TIRE SPECS

Performance Capability					
2S		4S		6S	
tmph	tkph	tmph	tkph	tmph	tkph
410	600	320	465	250	360

				Inflated Dimensions				Loaded Dimensions											
Rim Width & Flange		Min.Dual Spacing		Overall Width		Overall Diameter		Load & Sect & Growth		Static Load Rad		Revol Per		Gross Contact Area		Tire Volume		Tread Depth	
		in	mm	in	mm	in	mm	in	mm	in	mm	mi	km	in2	cm2	gal	ltrs	1/32in	mm
19.50-4.0		35/1	893	29/8	758	106/2	2697	33/9	861	48/7	1238	198	123	852	5500	525	1987	96	75

LOAD & INFLATIONS

30 MPH (50 KM/H) MAXIMUM SPEED OFF- THE ROAD HULAGE SERVICE											
PSI	65	69(*)	73	76	80	83	87	91	94	98	102(**)
LBS	43000	44100(*)	45400	48100	49400	50700	52000	55100	56800	58400	60000(**)
KPA	450	475(*)	500	525	550	575	600	625	650	675	700(**)
Pressure (bar)	4/5	4.75(*)	5	5/25	5/5	5/75	6	6/25	.6.5	6/75	7(**)
KG	19500	200000	20600	21800	22400	23000	23600	25000	25750	26500	27250(**)

= Estimated Data

نشانی تعمیرگاه و دفتر مرکزی

تهران، کیلومتر ۹ اتوبان فتح (جاده قدیم کرج)، خیابان شهید سامانی پور، خیابان البرز اول، کدپستی: ۱۳۷۹۸۴۳۴۱۳

+98 (21) - 48641010

www.FardaMachine.com

Instagram: FardaMachine_Official

+98 (21) - 4864 1011

info@FardaMachine.com

LinkedIn: FardaMachineOfficial